

# Pet Met Silver

(BOPET Metallized Polyester thermal laminating Film)

## Technical Data Sheet

### Profile

\* Biaxial-oriented chemical treated one side metalized polyester film with adhesive coating on other side.

### Features

- \*Silver metalized finish
- \*Good lamination bond strength
- \*Good machinability
- \*Suitable for printing, stamping and UV spot varnish (initial test required)

### Applications

\*Thermal lamination with all kinds of printed & unprinted paper, paperboards, book covers, posters, magazines, menu cards, boxes.

<u>Typical Properties +-3%</u>	<u>Unit</u>	<u>Test Method</u>	<u>Spec</u>
Unitweight	g/m <sup>2</sup>		26.20
Thickness	μ	MICRON	22
Yield	M <sup>2</sup> /kg	ASTM D-4321	38.2
Surface tension (adhesive coating inside)	Dynes/cm	ASTM D-2578	43
Laminating temperature	°e		95-115

### Recommendations:

- \*Storage: 12 months maximum in standard conditions (20°C, 40% relative humidity).
- \*The metallized side is sensitive to humidity and scratching and should be protected by another support.

Disclaimer: The information provided above is to the best of knowledge of the supplier. The values provided are test results, which are indicative only and provided for guidelines.

The aforementioned data is given most conscientiously but without any obligation. Any processing details are provided merely for guidance, it is the user's responsibility to check the suitability of the product for the intended application.

Warranty: This product has a warranty of 180 days from the date on the invoice.

Claims after 180 days from the date on the invoice for any reason cannot be accepted. Please always keep the full label details of the roll available for warranty purposes, without full label details we cannot handle or accept any claims.