

CERTIFICATE OF ANALYSIS

ISSUED NO : FM-2019-3312
 GRADE : EGM212
 ISSUED DATE :

ITEM	UNIT	METHOD	SPEC.	RESULT
THICKNESS AVERAGE_ACT	μm	DIC	20.37 ~ 21.63	21.60
TENSILE STRENGTH_MD	kg/mm ²	ASTMD882	Min 6.00	9.20
TENSILE STRENGTH_TD	kg/mm ²	ASTMD882	Min 9.00	14.50
TENSILE ELONGATION_MD	%	ASTMD882	Max 210.00	177.00
TENSILE ELONGATION_TD	%	ASTMD882	Max 80.00	63.00
HAZE	%	ASTMD1003	Min 75.00	81.00
GLOSS_60°	-	ASTMD2457	Max 9.00	8.80
WETTING TENSION_INSIDE	dyne/cm	ASTMD2578	Min 44.00	56.00
WETTING TENSION_OUTSIDE	dyne/cm	ASTMD2578	Min 38.00	41.00
INI. SEAL. TEMP.	°C	DIC	90.00 ~ 120.00	90.00
SEALING. STRENGTH	g/25mm	DIC	Min 600.00	763.00
----- BLANK -----				

CERTIFY THE STATEMENT OF QUALITY TO BE TRUE AND CORRECT.