

CHARACTERISTICS OF DIGI-MELT MATT LAMINATING FILM

1. TYPE : DIGI-MELT (Matt type of thermal laminating film)
2. APPLICATION : BOOK COVER & PRINTS, PHOTO and PAPERS
3. MELTING TEMPERATURE : 70 ~ 120°C or less on the Laminator
(Depend on the machine and its lamination speed)
4. SPECIFICATION

PROPERTIES		UNIT	TYPICAL VALUES	TEST METHOD
AVERAGE THICKNESS	X-BAR	μm	32 mic	PKC-METHOD
	R-BAR		2% +/-	
TREATMENT		DYNE/CM	I.S 44 ↑ , 0.S 38 ↑	
TENSILE STRENGTH	MD	kg/mm ²	10.8	ASTM
	TD		14.6	D-882
ELONGATION AT BREAK	MD	%	162	ASTM
	TD		48	D-882
Heat Shrinkage	MD	%	1.2	ASTM
	TD		0.1	D-1204
Coefficient of Friction	out/inside	us	1.58/0.22	ASTM
	opp/opp	uk	1.70/0.23	D-1894
Haze GLOSS	BASE FILM	%	88	ASTM D-1003
	45°		4.9	ASTM D-2457

*** The above data is based on Digi-melt Matt Laminating Film.

*** All properties are tested under standard laboratory conditions:

23 ±2°C : 50 ±5% RH, unless otherwise stated.

*** MD : Machine Direction, TD : Transverse Direction

*** The above data is for reference only.